



## **HYDRONOX HLP (IS 11656:1986 REAFFIRMED MARCH 2002) DIN 51524 part II**

### **DESCRIPTION:**

**LUBRINOX<sup>(R)</sup> HYDRONOX HLP** series lubricants are premium grade extra heavy duty hydraulic oils with exceptional thermal and oxidation stability. These lubricants are formulated to provide utmost satisfaction during operation when used in electro-hydraulic or numerically controlled hydraulic systems.

### **APPLICATION:**

- 1) Recommended for use in sophisticated modern days electro-hydraulic or numerically systems.
- 2) These oils can be used in any hydraulic systems mobile or industrial to achieve greater satisfaction.

### **BENEFITS:**

- 1) Excellent thermo-oxidative properties.
- 2) Compatible with almost all common sealing materials.
- 3) Provide longer life to pumps and total system.
- 4) Outstanding anti-wear properties.
- 5) Excellent demulsibility.

### **PRECAUTION:**

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

### **AVAILABLE PACK SIZE:**

20 Ltr, 50 Ltr, 210 Ltr

#### TYPICAL CHARACTERISTICS:

ISO VG GRADE	32	46	68
Appearance	Bright & clear	Bright & clear	Bright & clear
Kin. Viscosity, @ 40 <sup>0</sup> C, cst	32	46	68
Viscosity index , min.	105	104	103
Flash, COC , <sup>0</sup> C ,min.	210	218	220
Pour point <sup>0</sup> C , max	-21	-21	-18
Copper strip corrosion @ 100 <sup>0</sup> C, for 3 hrs	1a	1a	1a

\* These specifications are subject to variations/development/customisation.