

NOX CUT 25

PRODUCT DESCRIPTION:

LUBRINOX^(R) NOX CUT 25 is excellent neat cutting oil developed for the machining of ferrous metals (not for yellow metals). It contains active sulphur and fatty materials to provide better result under severe machining operations. Its low viscosity composition helps in swarf removal during the process.

APPLICATIONS:

- 1) It is highly recommended to be used for the machining of ferrous metals for deep hole drilling and other severe operations.

BENEFITS:

- 1) Improve tool life.
- 2) Better finish.
- 3) Sufficient cooling to the cutting tools.
- 4) Proper lubrication.
- 5) Reduced maintenance cost.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

Appearance	Bright & Clear
Kin Viscosity. @ 40 ⁰ C, cst	25
Flash Point ⁰ C, COC, min	170
Copper Corrosion @ 100 ⁰ C for 3 Hrs	4a

* These specifications are subject to variations/development/customisation.