

HYDRONOX AF 32, 46 & 68

DESCRIPTION:

LUBRINOX^(R) HYDRONOX AF 32, 46 & 68 viscosity grades are premium quality ash free hydraulic lubricants. These AF grade hydraulic oils are designed to meet the toughest requirements in the industries. These all ash free hydraulic oils are zinc free.

APPLICATIONS:

These ash free hydraulic oils are mostly recommended to be used for hydraulic system using vane and piston pumps where elevated operating temperature is encountered.

PERFORMANCE STANDARD:

D/N S 1502 – HLP

ISO 67 43/4 – HM & D/N 51524 Part 2

US Steel 126 & 127, Dimension HF-0

Cincinnati Lamb (Milacron) P68-69-70

BENEFITS:

- 1) Excellent anti-wear.
- 2) Very good thermo-oxidative Stability.
- 3) Excellent demulsibility.
- 4) Excellent filterability.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

ISO VG GRADE	32	46	68
Kin. Viscosity @ 40 ⁰ C, CST	32	46	68
Viscosity Index, min	110	105	100
Flash Point ⁰ C, COC, min	210	215	218
FZA Fail Stage	11	12	12
Pour Point, ⁰ C, max	-30	-27	-24

* These specifications are subject to variations/development/customisation.