



# **NOX CUT 45**

### **PRODUCT DESCRIPTION:**

**LUBRINOX**<sup>(R)</sup> **NOX CUT 45** is active type neat cutting oil developed to provide excellent finish to the tools under machining. It is non-staining cutting oil with very high EP property to provide easier machining of hard metals.

### **APPLICATIONS:**

1) It is recommended for the machining of high tensile stainless steel and nickel chromium alloys, drilling, thread cutting and gear hobbing operations.

#### **BENEFITS:**

- 1) Provides very good cooling.
- 2) Improved machined surfaces.
- 3) Increases tool life due to its EP properties.
- 4) Improves proper lubrication.
- 5) Protects against rust & corrosion.

# PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

#### **AVAILABLE PACK SIZE:**

20 Ltr, 50 Ltr, 210 Ltr

## **TYPICAL CHARACTERISTICS:**

Colour	Dark Amber.
K.V. @ 40°C	45
Flash Point <sup>o</sup> C, COC	170
Active Sulphur	No.
Inactive Sulphur	Yes.
Chlorine	Yes.

<sup>\*</sup> These specifications are subject to variations/development/customisation.

