

## NOX BROACH 20

### PRODUCT DESCRIPTION:

**LUBRINOX<sup>(R)</sup> NOX BROACH 20** is the severest amongst the various machining Operations. The cutting fluid has maximum anti-weld and extreme pressure properties in order to ensure high accuracy and excellent finish to the job. NOX BROACH 20 is chlorinated sulphurized neat cutting oil with pale/dark colour .

### APPLICATION:

- 1) Especially suitable for broaching and gear cutting steel, stainless steels and Nickel alloys.
- 2) It is recommended for non-ferrous metals.

### BENEFITS:

- 1) Long broach life
- 2) Excellent heat dissipation
- 3) Quick chips separation.
- 4) Low mist formation.
- 5) Provides optimization of product range
- 6) Economical in terms of cost per unit.

### PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

### AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

### TYPICAL CHARACTERISTICS:

Appearance	Bright & Clear
Kin. Viscosity @ 40°C, cst	21
Flash Point°C, COC, min	189
SAP Value mg KOH/gm	9
Copper Corrosion @ 100°C for 3 hours	4C

\* These specifications are subject to variations/development/customisation.