

## LUBRI CUT NS 50

### PRODUCT DESCRIPTION:

**LUBRINOX<sup>(R)</sup> LUBRI CUT NS 50** is special purpose **non-staining** type semi-synthetic neat cutting oil having very high oiliness property due to the presence of fatty material. The oil has excellent foam release ability and its use prevents overheating of work piece, thus eliminating chances of metal distortion.

### APPLICATIONS:

- 1) Recommended for flute grinding of drills, reamers and various types of grinding tools which involve severe metal grinding processes.
- 2) Suitable for gear cutting, hobbing and high speed metal working operations.
- 3) It can be used on both ferrous and non-ferrous metals.

### BENEFITS:

- 1) Very long sump life.
- 2) Excellent corrosion protection.
- 3) Longer tool life.
- 4) Keeps machine clean

### PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

### AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

### TYPICAL CHARACTERISTICS:

Appearance	Bright & Clear
Kin. Viscosity @ 40°C, cst	47
Flash Point°C, COC, min	202
SAP Value Report mg/KOH/gm	12

- These specifications are subject to variations/development/customisation