

NOX DRAW SS 100

PRODUCT DESCRIPTION:

LUBRINOX[®] NOX DRAW SS 100 is premium quality neat drawing oil specially developed for the drawing operations of stainless steel and its alloys. It is an active type of fluid which is highly fortified with sulphur and chlorine to impart high degree of extreme pressure and anti wear properties during the operation. It is highly enriched with lubricity agents.

APPLICATIONS:

- 1) Recommended for the drawing operations of stainless steels and its alloys only.
- 2) It is not suitable for the non ferrous metals.

BENEFITS:-

- 1) Increase tool life
- 2) Prevents wear.
- 3) Excellent surface finish.
- 4) Longer service life.
- 5) Operator's friendly.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

Appearance	Clear Liquid
Kin. Viscosity @ 40°C, cst	96
Flash Point°C, COC, min	200
SAP Value, mgKOH/gm	20
Copper Corrosion at 100°C. for 3 hrs	4c

These specifications are subject to variations/development/customisation.