

## HYDRONOX FR 46

### DESCRIPTION:

**LUBRINOX<sup>®</sup> HYDRONOX FR 46** is an advanced fire resistant hydraulic fluid based on water-glycol chemistry for the application in the areas where risk of fire is very high. It is enriched with very powerful additive to provide anti-wear, anti corrosion and anti-oxidants properties.

### APPLICATIONS:

- 1) Recommended to be used in hydraulic systems where fire risk is very high like metal and mining industries.
- 2) Maximum operating temperature is recommended to be 50°C to protect heavy evaporation of water.
- 3) Maximum operating temperature should not exceed 65°C.

### BENEFITS:

- 1) Significantly reduces fire risk.
- 2) Excellent anti-wear.
- 3) Very good protection against corrosion.
- 4) Proper lubrication to the components.
- 5) Extended fuel life.

### PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

### AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

### TYPICAL CHARACTERISTICS:

Appearance	Clear Liquid
Kin. Viscosity, cst @ 40°C	44
Pour Point°C, COC	-30
Density @29.5°C, gm/cm <sup>3</sup>	1.05

\* These specifications are subject to variations/development/customisation.