



NOX TAP 200

PRODUCT DESCRIPTION:

LUBRINOX^(R) **NOX TAP 200** is a premium quality tapping lubricants designed to provide excellent result on metal tapping applications. It is enriched with very high EP properties and lubricity to provide extended tool life. It is a non-corrosive lubricant hence can be used for cuprous metals also along with other difficult to machine metals such as stainless steel and other ferrous alloys.

APPLICATIONS:

- 1) Recommended for the tapping operation on most metals including aluminium, titanium and steel.
- 2) It can be used on copper also.

BENEFITS:

- 1) Multi-metal compatibility.
- 2) Excellent EP & anti-wear.
- 3) Extends tool life.
- 4) Proper lubrication.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

Appearance	Clear Liquid
Kin. Viscosity @ 40°C, cst	196
Flash Point ⁰ C, COC, min	210
Copper Corrosion @ 100°C for 3 hrs	1b

^{*} These specifications are subject to variations/development/customisation.

