



RUST PREVENTIVE DW 120

PRODUCT DESCRIPTION:

LUBRINOX^(R) **RUST PREVENTIVE DW 120** is an outstanding rust preventive fluid which has a remarkable acceptance in the industries for very long term protection against rust and corrosion. The soft greasy film left on the metal surface after the evaporation of solvent provides protection to the metals.

APPLICATIONS:

- 1) It is recommended to be used on ferrous metals during storage or before dispatch where shipment may take 3 to 4 months to reach to the destination through sea route.
- 2) It is also recommended in steel tubes industries for long term protection.

BENEFITS:

- 1) Excellent salt spray properties.
- 2) Very good acid fume resistance
- 3) Excellent dewatering
- 4) Easy to apply and remove.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS

Appearance	Clear amber colour fluid.
Flash Point ⁰ C, COC, min	40°C.
Film Thickness, mm	5-6
Salt Spray, hrs	120 Hours
Outdoor protection	6 Months
Indoor Protection	12 Months

^{*} These specifications are subject to variations/development/customisation.

