

LMS 40, 68 & 100

DESCRIPTION:

LUBRINOX^(R) LMS SERIES are very good quality general purpose machine oil series. These are formulated from solvent refined base stock and additives like detergent and dispersant to provide proper lubrication to machine parts and keep them clean for a longer period.

APPLICATIONS:

- 1) Recommended for use in any machinery for the lubrication purpose.

BENEFITS:

- 1) Avoid friction between two parts and thus prevents wear.
- 2) Sufficient lubrication to machine components.
- 3) Keep machine clean.
- 4) Prevents rust and corrosion.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

ISO VG GRADE	40	68	100
Appearance	Bright & Clear	Bright & Clear	Bright & Clear
Kin. Viscosity, @40°C, cst	40	68	100
Viscosity Index, min	95	95	95
Flash Point, °C, COC, min	190	210	214
Pour Point, °C, max	-6	-6	-6
Copper strip corrosion at 100°C, for 3 Hours	1a	1a	1a

* These specifications are subject to variations/development/customisation.