

NOX WAY 68

PRODUCT DESCRIPTION:

LUBRINOX[®] NOX WAY 68 is an excellent quality lubricant designed to meet the requirements of modern high production machine tool slide ways. It is designed from highly refined base stock and selected performance additives to provide excellent anti-wear and EP properties, very low frictional properties, filterability, demulsibility and adhesiveness characteristics. It is specially developed to prevent the “stick-slip” problems in slow moving, heavily loaded machine tool slides.

APPLICATIONS:

- 1) Recommended for slide ways of lathes, shapes, grinders.
- 2) Highly suitable for horizontal slides and ways on small to medium size tools.

BENEFITS:

- 1) Reduces chatter & stick-slip.
- 2) Provide improved surface finish.
- 3) Excellent demulsibility.
- 4) Very good anti-wear.
- 5) Excellent thermo oxidative stability.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

Kin. Viscosity @ 40°C, CST	68
Flash Point°C, COC, min	210
Pour Point °C, max	-12
Copper Corrosion @ 100°C for 3 Hrs	1b
Viscosity Index, min	97

* These specifications are subject to variations/development/customisation.