



## SUPER TURBO POWER 15W-40 (API CH-4)

### DESCRIPTION:

**LUBRINOX® SUPER TURBO POWER 15W40 CH-4** is a premium quality heavy duty diesel engine oil specially developed for modern low emission, turbo charged and naturally aspirated diesel engines. Its superior additive technology provides utmost engine protection and extended oil drain intervals. **LUBRINOX® SUPER TURBO POWER 15W40 CH-4** meets all the required standards of API CH-4.

### APPLICATION:

- Recommended for all turbo charged and naturally aspirated low emission diesel engines.
- Recommended for all high speed, high load and light to heavy duty vehicles.

### BENEFITS:

- Longer drain interval through high thermo-oxidative stability.
- Protects engine parts from wear and corrosion.
- Enhances engine cleanliness through excellent detergency.
- Reduces maintenance cost.

**CAUTION:** Avoid prolonged and repeated contact with used engine oil. Used engine oil contains potentially harmful contaminations. Keep out of reach of children. Used engine oil must be disposed off carefully to prevent damage to environment.

### TYPICAL CHARACTERISTICS:

Appearance	Bright & clear
Kin. Viscosity, @ 100° C, cst	14-15.5
Viscosity index, min	130
Flash point, coc, °C	210
Pour point °C, max	-27
TBN, mg kott/gm	10.0±1

\* These specifications are subject to variations/development/customization.

**AVAILABLE PACK SIZES: 1 LTR, 3 LTR, 5 LTR, 7.5 LTR, 10 LTR, 15 LTR, 20 LTR, 50 LTR & 210 LTR**